



NOTES:

1. MULCH LAYER SHALL BE HARDWOOD MULCH OR OTHER NON-FLOATING GROUND COVER.
2. AVOID INSTALLATION ON SLOPES GREATER THAN 3.00%. AVOID COMPACTING NATIVE SOILS. SCARIFY ANY COMPACTED SOIL.
3. LONGEST FLOW PATH OF CONTRIBUTING DRAINAGE AREA MUST NOT EXCEED 75 FEET.
4. GEOTEXTILE FABRIC SHALL MEET REQUIREMENTS OF IUM MATERIAL SPECIFICATION 592. FOR WOVEN: APPARENT OPENING SIZE OF 0.50 MM (TABLE 1, CLASS I). FOR NON WOVEN: APPARENT OPENING SIZE OF 0.30 MM (TABLE 2, CLASS II).
5. COARSE AGGREGATE OPTIONS ARE IDOT CA-1, CA-3, CA-7, OR APPROVED ALTERNATE. NO RECYCLED MATERIALS ARE ALLOWED.
6. FOLLOW THE REQUIRED PRETREATMENT MEASURES LISTED ON THE VOLUME CONTROL PRETREATMENT MEASURES DETAIL.

NOT TO SCALE

TECHNICAL GUIDANCE MANUAL

VEGETATED FILTER STRIP (FLOW-THROUGH) DETAIL

04/24/2026

STD. DWG. NO.15

PAGE NO. 16

