

# Nitrogen Removal Technology: Past, Present and Future- Blue Plains Advanced Wastewater Treatment Plant's Current Nutrient Regulation and Nitrogen Removal Processes

May 20<sup>th</sup>, 2011



**Sudhir N. Murthy, PhD, PE**

**DCWATER.COM**




- History and Basis of Nitrogen Removal at Blue Plains
- Nitrogen Removal Program Elements
  - Integration of evolving science within the nitrogen program
- New Frontiers




water is life

# Relative Responsibility for Pollution Loads to the Bay (2007)


### Nitrogen



### Phosphorus



### Sediment




Wastewater loads based on measured discharges; the rest are based on an average-hydrology year. Does not include loads from direct deposition to tidal waters, tidal shoreline erosion or the ocean. Data and Methods: [www.chesapeakebay.net/status\\_reducingpollution.aspx](http://www.chesapeakebay.net/status_reducingpollution.aspx)





# History of Nitrogen Removal at Blue Plains


- 1999 – Full scale operation of denitrification in same basins as nitrification
  - Met Chesapeake Bay goal of 40% reduction by 2000 from 1985 levels
  - Goal is 8.4672 million lbs/yr or 7.5 mg/L at 370 mgd
- Chesapeake 2000 - Tributary Strategies to lower TN load to the Bay by 2010. EPA and states agree to include annual cap load in NPDES permits
- **2011 TMDL requirements for Blue Plains AWTP**
  - 4.689 million lb TN limit for 001 and 002
    - **3.87 mg/L** at 370 mgd – average climatic year
    - **3.44 mg/l** at 435 mgd – wet climatic year





# Exceeding Chesapeake Bay Nitrogen Reduction Goal

## Annual Total Nitrogen Load, lbs/yr



# Blue Plains AWTP

- 370 mgd (AA) to 518 mgd (Max Day)
- TN < 7.5 mg/l & TP < 0.18 mg/l
- Future TN ~ 3 mg/l peak annual flows
- 12 C winter monthly average



Potomac River

Bar Screens and Grit Chambers

Primary Clarifiers

High-rate AS reactors

Secondary Clarifiers

Nitrification Denitrification AS reactors

Nitrification Denitrification Clarifiers

Final Dual-media Filters




- Nitrogen Removal Program Elements
  - Integration of evolving science within the nitrogen program



# Several Major Capital Programs Currently in Design

## 4 Key ENR Program Elements

1. Additional Denitrification Tanks
2. Sidestream Digester Recycle Treatment
3. Wet Weather Treatment
4. Secondary upgrades






# Wet Weather Management Plan



**New Wet Weather Pump Station  
& High Rate Enhanced  
Clarification Facility**



- Storm flows impact entire plant operation
  - Primary tanks are overloaded
  - Secondary and BNR sedimentation basins overloaded
  - Operators intervene to protect bio-processes
    - Reduced biological treatment capacity
    - Return to normal mode takes up to 5 days
  - 1% of annual BNR flow volume (flows > 555 mgd) causes ENR problems
- Site constraints
  - Land area is limited
  - Most of land is built-out
  - Limited space for new process trains
- **Must continue permit compliance while construction is underway**




- By Coordinating the Nitrogen Removal and Wet Weather Treatment planning, WASA could:
  - Provide better water quality performance than original CSO plan (LTCP), as required by EPA
  - Increase reliability of both TN & CSO controls
  - Achieve TN and CSO reductions earlier
  - Less impact on rate payers than conventional approach






# Total Nitrogen Removal: Nitrogen Removal Options

## Conventional Approach



## Innovative Approach






# Wet Weather Plan: Submitted 2007

## Extend tunnel by 3.5 miles:

- 23 feet diameter
- Added 31 million gallons to 126 million gallons of LTCP tunnels for total of 157 million gallons
- Increases storage capacity by about 25%

## Construct at Blue Plains:

- Nitrogen removal facilities
- Enhanced Clarification Facility (ECF)
- Tunnel Dewatering pumping station





# Wet Weather Management Plan

**New Wet Weather Pump Station  
& High Rate Enhanced  
Clarification Facility**

## Components of Wet Weather Treatment Plan

Item	Description
Tunnel Blue Plains and System Storage Volume	<ul style="list-style-type: none"><li>• New tunnel from Poplar Point to Blue Plains</li><li>• Requires increase in tunnels system storage volume of 31 mg (from 126 mg in LTCP to 157 mg)</li></ul>
Outfall Sewer Overflow to Blue Plains Tunnel	<ul style="list-style-type: none"><li>• Allow flows that exceed treatment capacity to overflow to tunnel (521 mgd min)</li></ul>
Tunnel Dewatering Pumping Station	<ul style="list-style-type: none"><li>• 225 mgd capacity at Blue Plains</li></ul>
Enhanced Clarification Facility	<ul style="list-style-type: none"><li>• 225 mgd capacity constructed at Blue Plains</li><li>• WASA will pilot test</li></ul>



# Meeting the New Chesapeake Bay Nitrogen Load Reduction Challenge

No	Item	Average Climatic Year	Wet Climatic Year (2003)	Notes
1	Rainfall (in)	40.97	59.3	
2	Base 002 Discharge in avg year (mgd)	370	370	
3	Est. 002 increment for wet weather (mgd)	0	65	From experience in 2003
4	Total 002 Flow (mgd)	370	435	( 2 ) + ( 3 )
5	001 Discharge (mgd)	7.3	17	From model
6	<b>Bubble Permit (EPA Approach)</b>			<b>001 + 002 must meet permit</b>
7	TN Permit Limit (lbs/yr)	4,689,000		Per permit
8	001 Effluent TN Allowance (lbs/yr)	311,420		Est. ECF performance
9	TN left for 002 (lbs/yr)	4,377,580		( 7 ) - ( 8 )
10	Effluent TN required at 002 (mg/L)	3.87	3.44	( 10 ) / ( 4 ) x conversions factors

**New Effluent TN Limit is very challenging especially in a wet year when the plant is most vulnerable to process upsets**




- Nitrogen Removal Program Elements
  - Integration of evolving science within the nitrogen program



# Fundamentals of Nitrification - Denitrification

**Autotrophic  
Aerobic Environment**

**Heterotrophic  
Anoxic Environment**





Oxygen demand 4.57 g / g  $\text{NH}_4^+\text{-N}$  oxidized  
Carbon demand 4.77 g COD / g  $\text{NO}_3^-\text{-N}$  reduced



# Fundamentals of Deammonification


**Autotrophic  
Aerobic Environment**

**ANAMMOX  
Anoxic Environment**  
 Anaerobic Ammonium Oxidation  
 Autotrophic Nitrite Reduction  
 (New Planctomycete, Strous et. al. 1999)






# ENR Upgrade and Expansion – Research & Planning





# The Nitrification/Denitrification Process

- Only 370 mgd facility in the world removing nitrogen and phosphorus to low levels
- Deep tank (33 ft) nit/denit system
- Twelve reactors were designed and optimized for equal flow split.





# ENR Research & Planning Program

## Defined Denitrification Kinetics

- Rate of Nitrogen removal defined by bacterial growth rates
- Industry standard denitrification rates assumed to be very fast
- Only small tank volumes required
- Blue Plains observed much slower rates






# Secondary Upgrade – Research & Planning

## 4 Key ENR Program Elements

1. Additional Denitrification Tanks
2. Sidestream Digester Recycle Treatment
3. Wet Weather Treatment
4. Secondary upgrades



**Expansion & Upgrade of the  
Secondary High Rate System  
& Clarifiers**

- Bioaugmentation

- Maximizes use of free wastewater carbon


- 1/3 less methanol

- Reduces size of new tanks

- Process is currently in operation



<b>(12) United States Patent</b>		<b>(10) Patent No.:</b>	<b>US 7,404,897 B2</b>
<b>Bailey, Jr. et al.</b>		<b>Date of Patent:</b>	<b>Jul. 29, 2008</b>
<b>(54) METHOD FOR NITROGEN REMOVAL AND TREATMENT OF DIGESTER REJECT WATER IN WASTEWATER USING BIOAUGMENTATION</b>		5,447,633 A	9/1995 Matsche et al.
		5,705,072 A	1/1998 Haase
		5,811,009 A *	9/1998 Kos
		6,163,932 A	12/2000 Rosen
		6,190,554 B1	2/2001 Mandt
		6,207,059 B1	3/2001 Moore, III
		6,426,004 B1 *	7/2002 Hant et al.
		6,602,417 B1 *	8/2003 Zibewant
		2007/0119763 A1 *	5/2007 Probst
<b>(75) Inventors:</b> <b>Walter F. Bailey, Jr.</b> , Washington, DC (US); <b>Sudhir N. Murthy</b> , Washington, DC (US); <b>Leonard Benson</b> , Washington, DC (US); <b>Timothy Constantine</b> , Toronto (CA); <b>Glen T. Daigler</b> , Englewood, CO (US); <b>Thomas E. Sadick</b> , Newport News, VA (US); <b>Dimitrios Katehis</b> , Chalfont, PA (US)		<b>FOREIGN PATENT DOCUMENTS</b>	
<b>(73) Assignee:</b> <b>D.C. Water &amp; Sewer Authority</b> , Washington, DC (US)		CZ 291489 1/2002	
<b>(*) Notice:</b> Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 92 days.		<b>OTHER PUBLICATIONS</b>	
<b>(21) Appl. No.:</b> <b>11/585,796</b>		S. Salem, et al., "Bio-Augmentation by Nitrification with Return Sludge," <i>Water Research</i> 37 (2003), pp. 1794-1804.	
<b>(22) Filed:</b> <b>Oct. 25, 2006</b>		(Continued)	
<b>(65) Prior Publication Data</b>		<b>Primary Examiner</b> —Chester T. Barry	
US 2007/0102356 A1 May 10, 2007		(74) <i>Attorney, Agent, or Firm</i> —Dickstein Shapiro LLP	
<b>Related U.S. Application Data</b>		<b>(57) ABSTRACT</b>	
<b>(60)</b> Provisional application No. 60/730,035, filed on Oct. 26, 2005.		An efficient system and process for removing nitrogen from wastewater while enriching seed sludge in the mainstream treatment process. Bioaugmentation of seed nitrifying organisms facilitate the nitrification reactions by enhancing the rates of reaction advantageously within a smaller volume or within a shorter activated sludge solids retention time. Likewise, bioaugmentation of seed denitrification organisms will also enhance rate of reaction within a smaller volume or shorter activated sludge solids retention time. Separate treatment of high ammonia digester reject water is an efficient method to treat nitrogen in recycle streams as well as to enrich the seed nitrifying and denitrifying cultures.	
<b>(51) Int. Cl.</b> <b>C02F 3/00</b> (2006.01)		<b>16 Claims, 4 Drawing Sheets</b>	
<b>(52) U.S. Cl.</b> <b>210/607; 210/610; 210/625; 210/626</b>			
<b>(58) Field of Classification Search</b> <b>210/607; 210/610; 625-626</b>			
See application file for complete search history.			
<b>(56) References Cited</b>			
U.S. PATENT DOCUMENTS			
4,537,682 A 8/1985 Wong-Chong			






# Side Stream Centrate Research & Planning




**New Side Stream  
Centrate  
Treatment  
Process**





# DEMON® Sequencing Batch Reactor – Energy Demand

- 84% TN Removal at design loading rate of 0.7 kg/ m<sup>3</sup> / day
- 1.3 kW hr / kg N removed
- However more sensitive to NO<sub>2</sub>-N accumulation < 5 mg/l






# DEMON® Sequencing Batch Reactor

water is life

- Plant undertook many energy efficiency activities
- With the introduction of DEMON it became a net energy producer



Bernhard Wett, March 2007



# Suspended Growth Deammonification Experience: DEMON® Process

## Suspended growth SBR systems:

- Strass, Austria
- Glarnerland, Switzerland
- Thun, Switzerland
- Plettenberg, Germany
- Heidelberg, Germany
- Apeldoorn, Netherlands
- Zalaegerszeg WWTP, Hungary

## Several under construction;

- Croatia
- Austria
- Germany
- By 2012 project > 20 Demon facilities on-line



Strass (A)



Apeldoorn (NL)



Heidelberg (D)





Thun (CH)

Need Long Solids Residence Time

Need to control nitrite toxicity

Need to inhibit competing NOB





## General Overview of DEMON the Site Visits & Design Criteria

Facility	Load (lbs/day)	Tank Vol. (MG)	Design Loading Rate (Kg N / m <sup>3</sup> / d	Performance % TN Removal % NH <sub>3</sub> -N Removal
Apeldoorn	4,180	0.77	0.66	> 80% TN > 90% NH <sub>3</sub> -N
Thun	880	0.16	0.67	> 90% TN > 90% NH <sub>3</sub> -N
Glarnerland	550	0.1	0.69	> 90% TN (80 mg/l) > 90% NH <sub>3</sub> -N (40mg/l)
Strass	1320	0.13	1.2	> 80% TN > 90% NH <sub>3</sub> -N
Blue Plains	20,000	5.8	0.58	>80% NH <sub>3</sub> -N
Alexandria	2831	0.8	0.42	> 90% TN

- Typical Volumetric Design Criteria = 0.7 Kg / m<sup>3</sup> / day
- Typically > 80% TN
- Effluent NO<sub>3</sub>-N < 10% or less if biodegradable COD available



Ongoing

BP Tunnel Dewatering Pump Station & Enhanced Clarification Facility

\$510 million

Dual Purpose Sed Basins Upgrade

\$18 million

New Filtrate Treatment Process

<\$64 million?

Cambi / MAD / BFP Dewatering

\$480 million

Enhanced Nutrient Removal Facilities

>\$350 million

Upgrade & expansion of the Nit/ Denit system

Upgrade of the Secondary High Rate System

\$66 million




# New Frontiers for Nutrient Removal





# What's Next? – Research & Planning








# Fundamentals of Deammonification

**Autotrophic  
Aerobic Environment**

**ANAEROBIC  
Anoxic Environment**  
 Anaerobic Ammonium Oxidation  
 Autotrophic Nitrite Reduction  
 (New Planctomycete, Strous et. al. 1999)








Strass, Austria  
Source: Bernhard Wett

**Sidestream characteristics – high temperature, higher  $\text{NH}_4^+$  and N/C ratio and adequate SRT**

**What about mainstream??**

**– lower temperature, low N/C ratio and limited SRT**





Source: Bernhard Wett, ARA Consult



- **WERF Project: INFR6R11**
- **Full-Plant Deammonification For Energy-Positive Nitrogen Removal**
  - **Principal Investigators: Maureen O'Shaughnessy and Bernhard Wett**
  - **Several utilities jointly investigating in Europe & USA**
  - **Full-scale, pilot-scale, bench-scale**
  - **Kartik Chandran, Columbia University**



# Can we apply Deammonification to Mainstream TN removal?

- International Collaboration



- Maureen O'Shaughnessy & Bernhard Wett / WERF & EPA
- **Blue Plains** bench scale SBRs started January 2011
- **HRSD Chez-Liz** pilot starting Summer 2011
- **Strass WWTP**, Austria started April 2011
- **Glarnerland WWTP**, Austria started to look at this 2010
- Initial concept:
  - Operate low C/N ratio
  - Optimize ammonia oxidizing autotrophs
  - Bioaugment and retain anammox
  - Out-compete nitrite oxidizing bacteria



Glarnerland WWTP, Austria




# Deammonification pilot at Blue Plains







water is life

# Reactor B – Profiling Specific Nitrogen Processing Rate





Anammox-granules visible in mainstream activated sludge



- Preliminary and promising data
- Three months of seeding
- Could take a year for steady state
- Nitrate concentration is significantly lower in deammonification lane



water is life

DEMON-cyclone installed for mainstream (left) and sidestream process (right)



## Potential Operating Cost Savings

Wastewater Plant	Annual Energy Savings*	Annual External Carbon Savings
Blue Plains (DC Water) (330 mgd)	\$4.0 - \$6.0 million	\$7.0 million
8 WWTPs (HRSD) (125 mgd)	\$2.0 - \$4.0 million	\$2.0 million
* Assumes 50% - 75% Anammox nitrogen removal.		

- New technologies for nitrogen removal are in development
  - Could considerably help reduce energy and carbon requirements for nitrogen removal
  - Could go a long way towards energy positive wastewater treatment
  - Compatible with existing infrastructure

# How does the *Program* work?

- Collaboration (Teams)
  - Within DC Water (DWT, Program Management)
  - Other Utilities (ASA, WSSC, Fairfax County, HRSD)
  - Universities
  - Modeling Experts
  - External Research Agencies (primarily WERF)

Approximately 200 publications and presentations in the past 8 years

# How does this *Program* work?

- Example Universities
  - Howard University
  - George Washington University
  - University of Maryland
  
  - Virginia Tech
  - Virginia Military Institute
  - Bucknell University
  
  - University of Innsbruck
  - University of Waterloo
  - Laurier University

Approximately 30 MS and PhDs in 8 years



**Contact: Sudhir N. Murthy, PhD, PE  
DC Water**



water is life

---

